

|                     |  |
|---------------------|--|
| Product SKU         | LNGD614                                    |
| Thickness           | 3mm  |
| Length              | 710mm                                      |
| Width               | 158mm                                      |
| Wear layer          | 0.7mm                                      |
| Colour              | Vintage Grey Oak                           |
| Edge profile        | Square Bevel                               |
| UFH max temp.       | 27°C                                       |
| Pack weight         | 18.97kg                                    |
| Pack size           | 3.37m <sup>2</sup>                         |
| Warranty            | Domestic: Lifetime<br>Commercial: 15 years |
| Installation method | Glued Down                                 |



| Test Item                   | Testing Method        | Testing Result  |
|-----------------------------|-----------------------|---|
| Surface treatment:          | -                     | Urethane ceramic bead/Excimer coating   |
| Performance classification: | ISO10582              | 33: Commercial heavy<br>23: Domestic heavy  |
| Dimensional stability:      | ISO 23999 ASTM F 2199 | ≤0.2%   |
| Heat curl:                  | ISO 23999             | ≤2mm  |
| Static load:                | ISO 24343-1           | ≤0.13 mm  |
| Resistance to impact:       | ISO 24344             | No crack  |
| Residual indentation:       | ISO 24343-1           | ≤0.05mm   |
| Abrasion resistance:        | EN 660-2              | Group T Pass  |
| Light fastness:             | ISO 105-B02           | ≥6  |
| Reaction to fire:           | ISO9239-1             | Bfl -S1   |
| Resistance to staining:     | ISO 26987:2008        | Pass  |
| Slip resistance:            | EN 13893<br>DIN 51130 | Class DS<br>R10   |
| Chemical resistance:        | ISO4918               | Pass. No more than a slight change in surface dulling, surface attack or staining |
| Castor chair test:          | ISO 4918:2016         | Pass No visible damage after 25000 cycles   |
| VOC emission:               | FloorScore            | Certified   |
|                             | TUV PROFICERT         | Certified   |
| Environment:                | EPD                   | Certified   |